

192J9130



#### Strong points

- Easy to use
- Advanced functionalities

#### General characteristics

- Large backlit LCD display
- Direct display of multi-measurement and metering values
- RS485 Modbus communication
- Inputs/output for control/command or impulse

#### Compliance with standards

- IEC 62053-21 Class 1
- IEC 62053-23 Class 2

#### Link to the reference

The MULTIS L is a panel mounted digital meter displaying multi-measurement and energy values directly on its large backlit LCD display. It is designed for use on three-phase or single-phase networks with connection via CT and is suitable for applications of up to 6000 A. The product can be configured by the user via the keypad and the display.

#### Classification

|            |          |
|------------|----------|
| UNSPSC     | 83101808 |
| ETIM Class | EC002301 |
| IGCC       | 6042     |

#### Commerce

|                   |            |
|-------------------|------------|
| Effective date    | 2018-05-07 |
| Country of origin | TN         |

#### ETIM - Technical features

|              |     |
|--------------|-----|
| Ampere meter | Yes |
| Voltmeter    | Yes |

#### Logistics

|                            |               |
|----------------------------|---------------|
| GTIN/EAN                   | 3596033056970 |
| Customs number             | 9030310090    |
| Price unit                 | PC            |
| Weight of the packing unit | 0.6           |

#### Norms

|                         |     |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

#### Technical Characteristics

|                         |     |
|-------------------------|-----|
| Application             | N/A |
| Communication ports     | N/A |
| Communication protocols | N/A |
| Model                   | N/A |
| Type                    | N/A |

<https://apac.socomec.com/en/reference/192J9130>