

192T3430

Bar or cable-through CT TCB3 22-30 3x300A/3x5A Class 1 3,75VA

Classification



Current transformers deliver to the secondary a standard current proportional to the primary current and adapted to the rating of the associated device. They are equipped as standard with removable terminal covers and double terminals allowing the secondary to be short-circuited without any risk.

They are mounted using two screw-on metal brackets or, in certain cases, by a clipon DINrail fastener. The connections are made by screws or by fast-on terminals.

Strong points

- Compatible accuracy class
- Wide range of ratings and dimensions
- Quick and easy to install

General characteristics

- Accuracy class: 0.2s 0.5 or 1.
- Dielectric quality: 3 kV 50 Hz 1 min.
- Operating frequency: 50 60 Hz.
- Permanent overload: 1.2 In.
- Insulation class: E (120 °C).

Compliance with standards

- IEC 61869-2
- IEC 61439-1

Link to the reference

Olabbilloation	
UNSPSC	39121032
ETIM Class	EC002048
IGCC	4186
Commerce	
Effective date	2010-06-02
Country of origin	HU
ETIM - Electrical characteristics	
Rated primary current [A]	300
Rated secondary current [A]	5
Rated secondary apparent power [VA]	3.75
Accuracy class	1
Overcurrent limiting factor	FS 5
Calibrated	No
ETIM - Mechanical characteristics	
With contact protection	No
Height opening [mm]	3030
Width opening [mm]	3030
Opening diameter [mm]	22
Snap mounting	Yes
With copper rail	Yes
Secondary connection	Screw connection
ETIM - Technical features	
Model	3-phase current converter set
Number of primary inputs	3
Logistics	
GTIN/EAN	3596032009502
Customs number	8504318090
Price unit	PC
Weight of the packing unit	0.634
Length of the packing unit	0.155
Width of the packing unit	0.075
Depth of the packing unit	0.06
Norms	
Conformity to standards	IEC
Technical Characteristics	
Model	TCB 322-30 (3phase CT)
Opening	30x10 - Diam.22 (3x)
Rated current	300

5

https://apac.socomec.com/en/reference/ 192T3430

2024-05-05 17:15:56

Secondary rated current