

37104003

Fusible discon switch FUSERBLOC-Ext&Dir F/L R&L OP-30A-3+NCP-UL-Fuse CC

Strong points

- Improved safety
- High breaking capacity
- Multi-use
- Simplified use

General characteristics

- For fuses up to 800 A.
- Up to 200 kA.
- AC voltage from 208 V to 600 V.
- Accepts Class CC, J and L fuses.
- 2P, 3P or 4P available.

Compliance with standards

- IEC 60947-3
- UL489 (box 1 and 2)
- UL 98 (box 4 to 8)
- CSA 22.2 #4 (box 1 and 2)
- CSA 22.2 #5 (box 4 to 8)
- NFPA 79 (2002 version)

Link to the reference

<https://apac.socomec.com/en/reference/>

[37104003](#)

FUSERBLOC UL units are manually-operated multipole fuse load break switches with external right front-side operation and comply with UL and CSA standards. They provide make and break on load and safety isolation and protection against overcurrent for any low voltage electrical circuit. The switches use double-pole isolator contacts to ensure complete isolation of the fuse when the switch is in the "OFF" position.

These devices are suitable for use as disconnectors for motors and industrial control panels on service entrance equipment, final panelboards, distribution switchboards, industrial control equipment or motor control centres.

This range is available in right front-side, direct or external control, in 2, 3 and 4 poles and up to 800 A.

Classification	
UNSPSC	39122233
ETIM Class	EC001040
IGCC	5291
Commerce	
Effective date	2000-09-01
Country of origin	FR
Length of the product unit	0.116
Width of the product unit	0.096
Depth of the product unit	0.0835
Weight	0.6
ETIM - Electrical characteristics	
Max. rated operation voltage Ue AC [V]	600
Rated permanent current Iu [A]	30
Conditioned rated short-circuit current Iq [kA]	100
Number of poles	4
ETIM - Mechanical characteristics	
Cable entry	Top/bottom
Equipped with connectors	No
Suitable for floor mounting	Yes
Suitable for front mounting	Yes
Suitable for busbar mounting	No
Degree of protection (IP), front side	IP20
ETIM - Technical features	
Version as main switch	Yes
Version as safety switch	Yes
Suitable for fuses	Other
With error protection	No
Type of electrical connection of main circuit	Frame clamp
Type of control element	Short thumb-grip
Position control element	Front side
Motor drive optional	No
Motor drive integrated	No
Version as emergency stop installation	Yes
Logistics	
GTIN/EAN	3596031544783

Customs number	8536303099
Price unit	PC
Weight of the packing unit	0.6
Length of the packing unit	0.155
Width of the packing unit	0.12
Depth of the packing unit	0.135

Norms

Conformity to standards	UL
-------------------------	----

Technical Characteristics

Control operator	Direct : P1 / External : S1
Fuse size	CC
Number of poles	3+NCP
Rated current	30
Type	I-0
Frame size	1