


42154063

Manual transfer switch SIRCOVER I-0-II 4P 630A in polyester enclosure



Strong points

- Safe operation
- Suitable for all environments
- Easy installation
- Extensive range

General characteristics

- From 160 to 630 A.
- 3 poles, 4 poles.
- SIRCOVER with break-before-make operation (I-0-II), other options on request.
- Black handle.
- Triple lock in OFF position.
- Polyester enclosure.
- Screw-on front, door interlocked when ON.
- Colour: RAL 7035.
- IP rating: IP55.
- Wall-mounted, 4 brackets included.

Compliance with standards

- IEC 60947-6-1
- IEC 61439
- IEC 60204-1

Link to the reference

<https://apac.socomec.com/en/reference/42154063>

Enclosed changeover switches ensure the on-load transfer between two sources or loads, as well as providing safety isolation, for all low-voltage electrical circuits. In addition, they provide protection against contact with live parts and environmental elements such as dust, water and other hazards. They enable the shutdown and lock out of the power supply as close to the equipment as possible.

====- System -====

Fill rate E-Order Common	100
Fill rate E-Order Selection	100

Classification

UNSPSC	39122205
ETIM Class	EC000216
IGCC	5177

Commerce

Effective date	1999-10-01
Country of origin	FR
Discount Policy	1CM40
Discount Policy Label	ENCLOSED MANUAL COS
Length of the product unit	0.8
Width of the product unit	0.6
Depth of the product unit	0.3
Weight	26.37

ETIM - Electrical characteristics

Max. rated operation voltage Ue AC [V]	1000
Rated operating voltage [V]	400..690
Rated permanent current Iu [A]	630
Rated permanent current at AC-23, 400 V [A]	630
Rated permanent current at AC-21, 400 V [A]	630
Rated short-time withstand current Icw [kA]	10
Rated operation power at AC-23, 400 V [kW]	450
Switching power at 400 V [kW]	450
Number of poles	4

ETIM - Mechanical characteristics

Suitable for floor mounting	Yes
Suitable for front mounting 4-hole	Yes
Suitable for front mounting centre	No
Suitable for distribution board installation	No
Suitable for intermediate mounting	No
Colour control element	Black
Degree of protection (IP), front side	IP55

ETIM - Technical features

Version as main switch	No
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	No
Version as reversing switch	Yes
Number of switches	2
Motor drive optional	No

Motor drive integrated	No
Voltage release optional	No
Device construction	Complete device in housing
Type of control element	Door coupling rotary drive
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection

Logistics

GTIN/EAN	3596031210176
Customs number	8536508090
Price unit	PC
Weight of the packing unit	26.37
Length of the packing unit	0.37
Width of the packing unit	0.6
Depth of the packing unit	0.8

Norms

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Control operator	Front
Number of poles	4
Rated current	630
Size	800x600x300
Frame size	B5