

48290102

Voltage acquisition module DIRIS Digiware U-30 Analysis



Strong points

- Safe
- Compact
- A complete dedicated solution

General characteristics

- Voltage accuracy class 0.2
- Frequency accuracy class 0.02
- Compatible with all supply system types

Compliance with standards

- IEC 61557-12
- UL 61010 Guide PICQ File E257746

Link to the reference

<https://apac.socomec.com/en/reference/48290102>

The DIRIS Digiware Uac module measures voltage for the entire system. This pools together all voltage measurements.

The Digiware RJ45 Bus allows you to pass voltage measurements as well as power supply and communication to all connected products.

----- System -----

Fill rate E-Order Common	33
Fill rate E-Order Selection	60

Classification

UNSPSC	83101808
ETIM Class	EC002301
IGCC	6042

Commerce

Effective date	2013-11-22
Country of origin	FR
Discount Policy	1EN60
Discount Policy Label	MEASUREMENT SYSTEM PACKAGE

ETIM - Electrical characteristics

Sampling frequency [Hz]	10000
Number of voltage measurement inputs	4
Voltage type (supply voltage)	DC
Supply voltage DC [V]	0..24
Measuring range for frequency [Hz]	45..65
Supporting protocol for IEC 61850 Ethernet	No
Supporting protocol for OPC UA PubSub	No
Supporting protocol for PROFIBUS	No
Supporting protocol for Modbus	Yes
Supporting protocol for PROFINET IO	No
Supporting protocol for other bus systems	No
With audit logging (audit log)	No
With firmware signature	Yes
With logging of security events (security event log)	No
With Role Based Access Control (RBAC)	No
Web server with HTTPS transfer protocol	No

ETIM - Mechanical characteristics

Width [mm]	18
Height [mm]	90
Depth [mm]	65

ETIM - Technical features

Ampere meter	No
Blind power meter	Yes
With rotational speed meter	No
Frequency meter	Yes
Pulse counter	No
Voltmeter	Yes
Effective power measurement device	No
Display	None
Remote display	No

Logistics	
GTIN/EAN	3596032776374
Customs number	9030337000
Price unit	PC
Weight of the packing unit	0.09
Length of the packing unit	0.035
Width of the packing unit	0.08
Depth of the packing unit	0.12
Norms	
Conformity to standards	IEC UL
Technical Characteristics	
Application	Analysis
Model	U-30
Rated voltage	87..520 VAC (L-L)
Type	AC voltage acquisition module