

# 48290112

# Current module DIRIS Digiware I-60, 6 current inputs, Metering



### Strong points

- Multi-circuit
- Accurate
- Compact
- Plug & Play
- Leading edge technology
- MID certified and more

#### General characteristics

- Versions with 3, 4 or 6 RJ12 current inputs.
- Compatible with TE, TR/iTR and TF current sensors.
- DIN rail assembly.

#### Compliance with standards

- IEC 61557-12
- UL 61010 Guide PICQ File E257746
- ANSI C12.20
- EN 50470-1
- EN 50770-3
- Directive 2014/32/EU

## Link to the reference

2024-04-27 23:24:32



https://apac.socomec.com/en/reference/ 48290112

DIRIS Digiware lac modules measure consumption and monitor the installation as close as possible to loads. Their flexibility allows you to distribute the loads to meter or monitor independent current inputs (for example: 1 three-phase load or 3 single-phase loads).

ill rate E-Order Common	25
ill rate E-Order Selection	60
Classification	
JNSPSC	83101808
ETIM Class	EC002301
GCC	6042
Commerce	
Effective date	2014-01-23
Country of origin	FR
Discount Policy	1EN60
Discount Policy Label	MEASUREMENT SYSTEM PACKAGE
ETIM - Electrical characteristics	
Sampling frequency [Hz]	10000
Number of current measurement inputs	6
/oltage type (supply voltage)	DC
Supply voltage DC [V]	0.240.24
Supporting protocol for IEC 61850 Ethernet	No
Supporting protocol for OPC UA PubSub	No
Supporting protocol for PROFIBUS	No
Supporting protocol for Modbus	Yes
Supporting protocol for PROFINET IO	No
Supporting protocol for other bus systems	No
Nith audit logging (audit log)	No
Nith firmware signature	Yes
Nith logging of security events (security event og)	Yes
With Role Based Access Control (RBAC)	No
Web server with HTTPS transfer protocol	No
ETIM - Mechanical characteristics	
Nidth [mm]	36
Height [mm]	90
Depth [mm]	65
Degree of protection (IP), front side	IP20
ETIM - Technical features	
Ampere meter	Yes
Blind power meter	Yes
With rotational speed meter	No
requency meter	No
Pulse counter	No
/oltmeter	No
Effective power measurement device	Yes
Remote display	No

2024-04-27 23:24:32 2/3



GTIN/EAN	3596032783853	
Customs number	9030337000	
Price unit	PC	
Weight of the packing unit	0.112	
Length of the packing unit	0.045	
Width of the packing unit	0.08	
Depth of the packing unit	0.13	
Norms		
Conformity to standards	IEC UL	
Technical Characteristics		
Application	Metering	
Model	I-60	
Number of current inputs	6	
Туре	Current acquisition module	

2024-04-27 23:24:32 3/3