

57010019

## RM cylind. fuse holder without aux. cont.-32A-3PP+N-NFC-Fuse 10x38



### Strong points

- Improved safety
- High breaking capacity
- Format and specific accessories

### General characteristics

- Improved safety.
- High breaking capacity.
- Features and options.

### Compliance with standards

- IEC 60269-2,-1
- IEC 60269-1
- IEC 60269-2
- UL E307648

### Link to the reference

<https://apac.socomec.com/en/reference/57010019>

RMs are modular fuse disconnect switches for cylindrical fuses. They ensure safe disconnection and protection against surges and short-circuits in any low voltage electrical circuit.

### Classification

UNSPSC	39121624
ETIM Class	EC002705
IGCC	4974

### Commerce

Effective date	2012-06-25
Country of origin	ES
Length of the product unit	0.078
Width of the product unit	0.07
Depth of the product unit	0.058
Weight	0.23

### ETIM - Electrical characteristics

Nominal voltage [V]	690
Number of poles	4
Concurrently switching neutral conductor	Yes

### ETIM - Mechanical characteristics

Built-in depth [mm]	40
Degree of protection (IP)	IP2X
Mounting method	DIN rail
For fuse size	10x38 mm
Width in number of modular spacings	4

### ETIM - Technical features

Lockable	Yes
With optical defect indication	No

### Logistics

GTIN/EAN	3596032686925
Customs number	8536105090
Price unit	PC
Weight of the packing unit	0.27
Length of the packing unit	0.09
Width of the packing unit	0.075
Depth of the packing unit	0.065

### Norms

Conformity to standards	IEC UL
-------------------------	------------

### Technical Characteristics

Fuse melting indicator	No
Fuse size	10x38
Number of poles	3+N
Rated current	32
Size	RM32