


57025012

## Dead front fuse holder front operated 14x51 2P 50 A for RMS50



### Strong points

- Improved safety
- High breaking capacity
- Format and specific accessories

### General characteristics

- Improved safety.
- High breaking capacity.
- Features and options.

### Compliance with standards

- IEC 60269-2,-1
- IEC 60269-1
- IEC 60269-2
- UL E307648

### Link to the reference

<https://apac.socomec.com/en/reference/57025012>

RMS are modular fuse disconnect switches for cylindrical fuses. They provide safety disconnection and protection against overloads and short-circuits in any low voltage electrical circuit.

RMS: Fuse disconnect switches with pre-breaking auxiliary contact that signals that the fuse is present / blown.

### Classification

|            |          |
|------------|----------|
| UNSPSC     | 39121624 |
| ETIM Class | EC002705 |
| IGCC       | 4974     |

### Commerce

|                            |            |
|----------------------------|------------|
| Effective date             | 2005-11-23 |
| Country of origin          | ES         |
| Length of the product unit | 0.11       |
| Width of the product unit  | 0.106      |
| Depth of the product unit  | 0.076      |
| Weight                     | 0.22       |

### ETIM - Electrical characteristics

|  |     |
|--|-----|
| Nominal voltage [V]                      | 690 |
| Number of poles                          | 2   |
| Concurrently switching neutral conductor | No  |

### ETIM - Mechanical characteristics

|                                     |          |
|-------------------------------------|----------|
| Built-in depth [mm]                 | 49.5     |
| Degree of protection (IP)           | IP2X     |
| Mounting method                     | DIN rail |
| For fuse size                       | 14x51 mm |
| Width in number of modular spacings | 2        |

### ETIM - Technical features

|                                |     |
|--------------------------------|-----|
| Lockable                       | Yes |
| With optical defect indication | Yes |

### Logistics

|                            |               |
|----------------------------|---------------|
| GTIN/EAN                   | 3596031808137 |
| Customs number             | 8536105090    |
| Price unit                 | PC            |
| Weight of the packing unit | 0.22          |
| Length of the packing unit | 0.11          |
| Width of the packing unit  | 0.077         |
| Depth of the packing unit  | 0.055         |

### Norms

|                         |            |
|-------------------------|------------|
| Conformity to standards | IEC<br/>UL |
|-------------------------|------------|

### Technical Characteristics

|                        |           |
|------------------------|-----------|
| Fuse melting indicator | Yes       |
| Fuse size              | 14x51     |
| Number of poles        | 2         |
| Rated current          | 50        |
| Size                   | RM/RMS 50 |