

60120006

Cylindrical fuse without striker gG type 10x38 500Vac 6A



Strong points

- High-performance
- Increased reliability
- Improved safety

General characteristics

- High-performance.
- High level of reliability.
- Improved safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2

Link to the reference

<https://apac.socomec.com/en/reference/60120006>

Industrial fuses protect installations and people from overcurrents for any low voltage electrical circuit.

===== System =====

| | |
|-----------------------------|-----|
| Fill rate E-Order Common | 83 |
| Fill rate E-Order Selection | 100 |

Classification

| | |
|------------|----------|
| UNSPSC | 39121609 |
| ETIM Class | EC002704 |
| IGCC | 4905 |

Commerce

| | |
|----------------------------|------------------|
| Effective date | 1988-04-15 |
| Country of origin | ES |
| Discount Policy | 1CF10 |
| Discount Policy Label | CYLINDRICAL FUSE |
| Length of the product unit | 0.038 |
| Width of the product unit | 0.0103 |
| Weight | 0.01 |

ETIM - Electrical characteristics

| | |
|---------------------------------|--------|
| Breaking capacity [kA] | 120 |
| Power loss at rated current [W] | 0.85 |
| Voltage type | AC |
| Rated current [A] | 6 |
| Rated voltage [V] | 500 |
| Rated operating frequency [Hz] | 50..60 |

ETIM - Mechanical characteristics

| | |
|------|----------|
| Size | 14x51 mm |
|------|----------|

ETIM - Technical features

| | |
|-------|--------------|
| Model | Ceramic fuse |
|-------|--------------|

Logistics

| | |
|----------------------------|---------------|
| GTIN/EAN | 3596031377091 |
| Customs number | 8536101090 |
| Price unit | PC |
| Weight of the packing unit | 0.01 |
| Length of the packing unit | 0.01 |
| Width of the packing unit | 0.01 |
| Depth of the packing unit | 0.04 |

Norms

| | |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

Technical Characteristics

| | |
|------------------------|-----------------|
| Fuse melting indicator | without striker |
| Fuse size | 10x38 |
| Rated voltage | 500 VAC |
| Rated current | 6 |
| Type | gG |