

60PV1200

Photovoltaic knife edge fuse gPV S1 1000VDC 200A



Strong points

- High breaking capacity
- Product designed for photovoltaic systems
- Increased reliability
- Improved safety

General characteristics

- ISC MAX: short-circuit current of the string related to excess sunshine.
- MRI: maximum permissible reverse
- In: fuse rating or nominal fuse current (at 25°C in an RM fuse base).
- Nc: number of strings in parallel.
- UE: maximum fuse operating voltage.
- UOC MAX: maximum voltage of an open circuit in lowest temperature conditions

Compliance with standards

- IEC 60269-6

2024-05-04 07:02:49



- IEC 60269-1
- IEC 60269-2

Link to the reference

gPV fuses protect facilities against surges related to reverse currents that can occur in photovoltaic systems.

When to protect

You must protect the PV strings from surges if the current delivered by the set minus one of the parallel strings is greater than the reverse current supported by the type of modules used in this generator.

How to protect

Protecting from overcurrents involves ensuring that both polarities are functionally grounded whether the DC is connected or not.

https://apac.socomec.com/en/reference/60PV1200

JNSPSC	39121612
ETIM Class	EC000055
GCC	4908
Commerce	
Effective date	2015-03-16
Country of origin	IN
ength of the product unit	0.053
Vidth of the product unit	0.137
Depth of the product unit	0.04
Veight	1.28
ETIM - Electrical characteristics	
/oltage type	DC
Rated current [A]	200
Rated voltage DC [V]	1000
Jtilization category	gPV (photovoltaic protection)
ETIM - Technical features	
Fuse construction type according to IEC 60269	NH1
Logistics	
GTIN/EAN	3596032851064
Customs number	8536109090
Price unit	PC
Neight of the packing unit	1.28
ength of the packing unit	0.135
Nidth of the packing unit	0.065
Depth of the packing unit	0.04
Norms	
Conformity to standards	IEC
Fechnical Characteristics	
Fuse melting indicator	with T indicator
- use size	NH1
Rated voltage	1000 VDC
Rated current	200
Гуре	gPV

2024-05-04 07:02:49