

65001130

Fuse base for fuses without a striker T00 3P 160A DIN rail-mounted device



Strong points

- High level of electrical safety
- High breaking capacity
- Fuse blown indicator
- Various mounting options

General characteristics

- High level of electrical safety.
- High breaking capacity.
- Fuse blown indicator.
- Various mounting options.

Compliance with standards

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2,-1

Link to the reference

2024-05-04 13:04:32



https://apac.socomec.com/en/reference/65001130

Fuse bases are single-pole or multi-pole solid supports for knife-edge fuses.

| JNSPSC | 39121624 |
|----------------------------------|---------------|
| TIM Class | EC000067 |
| GCC | 4972 |
| Commerce | |
| Effective date | 2003-01-09 |
| Country of origin | ES |
| Veight | 0.44 |
| ETIM - Electrical characteristic | cs |
| Number of poles | 3 |
| Rated current [A] | 160 |
| ETIM - Mechanical characteris | tics |
| Construction size | NH00 |
| ETIM - Technical features | |
| Bus-mounting type | No |
| Swivelling mechanism | No |
| ogistics | |
| GTIN/EAN | 3596031652297 |
| Customs number | 8536109090 |
| Price unit | PC |
| Weight of the packing unit | 0.44 |
| ength of the packing unit | 0.125 |
| Nidth of the packing unit | 0.165 |
| Depth of the packing unit | 0.07 |
| Norms | |
| Conformity to standards | IEC |
| Technical Characteristics | |
| use size | NH00 |
| Number of poles | 3 |
| Rated current | 160 |

2024-05-04 13:04:32