

66010020

Knife-edge fuse without striker aM type NH S000/00C 500Vac 20A



Strong points

- High-performance
- Increased reliability
- Improved safety

General characteristics

- High-performance.
- High level of reliability.
- Improved safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2

Link to the reference

2024-05-02 17:13:03



https://apac.socomec.com/en/reference/66010020

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

| NSPSC | 39121612 |
|---|----------------------------|
| TIM Class | EC000055 |
| GCC | 4908 |
| Commerce | |
| Effective date | 1995-10-19 |
| Country of origin | HU |
| ength of the product unit | 0.048 |
| Vidth of the product unit | 0.08 |
| Depth of the product unit | 0.03 |
| Veight | 0.121 |
| ETIM - Electrical characteristics | |
| /oltage type | AC |
| Rated current [A] | 20 |
| Rated voltage AC [V] | 500 |
| Jtilization category | aM (switchgear protection) |
| ETIM - Mechanical characteristics | |
| Type of fuse status indicator | None |
| ETIM - Technical features | |
| Fuse construction type according to IEC 60269 | NHC00 |
| ogistics | |
| GTIN/EAN | 3596031383757 |
| Customs number | 8536105090 |
| Price unit | PC |
| Weight of the packing unit | 0.121 |
| ength of the packing unit | 0.09 |
| Vidth of the packing unit | 0.07 |
| Depth of the packing unit | 0.06 |
| Norms | |
| Conformity to standards | IEC |
| Technical Characteristics | |
| use melting indicator | without striker |
| Fuse size | SOOC |
| | 500 VAC |
| Rated voltage | |
| Rated current | 20 |

2024-05-02 17:13:03 2/2